

F-1

• On a horizontal surface



F-2


• Mounted on the wall or ceiling




T-1 CP-TW2505, CP-TW3005 (1280 x 800) (±8%)

Screen size (diagonal) ⓐ		Projection distance				Screen height			
		ⓑ1		ⓑ2		ⓒ1		ⓒ2	
type(inch)	m	m	inch	m	inch	m	inch	m	inch
60	1.5	0.128	5.0	0.409	16.1	0.313	12.3	1.121	44.1
70	1.8	0.198	7.8	0.479	18.9	0.351	13.8	1.293	50.9
80	2.0	0.268	10.5	0.549	21.6	0.388	15.3	1.465	57.7
90	2.3	0.338	13.3	0.619	24.4	0.426	16.8	1.638	64.5
100	2.5	0.408	16.1	0.689	27.1	0.464	18.3	1.810	71.3


F-3


VCR/DVD/Blu-ray
Disc player
Computer
AUDIO OUT
L
R
VIDEO
COMPONENT
Cb/Pb Cr/Pr
Y
HDMI
AUDIO OUT
VIDEO IN
AUDIO IN 2
L
R
USB TYPE A
DC5V 0.5A
LAN
AUDIO IN 1
COMPUTER IN 1
CONTROL
MIC
HDMI 2
HDMI 1 / MHL
USB TYPE B
AUDIO OUT
DISPLAY
RS-232C
USB (A)
HDMI
Smartphone
Tablet


F-4


Microphone
system
Speakers
(with an amplifier)
R
L
Monitor
RGB IN
AUDIO IN 2
L
R
VIDEO IN
USB TYPE A
DC5V 0.5A
LAN
COMPUTER IN 1
CONTROL
MIC
HDMI 2
HDMI 1 / MHL
USB TYPE B


F-5


Computer
Access point
RS-232C
USB TYPE A
LAN
AUDIO OUT
COMPUTER IN 2 / MONITOR OUT
VIDEO IN
AUDIO IN 2
L
R
USB TYPE A DC5V 0.5A
LAN
AUDIO IN 1
COMPUTER IN 1
CONTROL
MIC
HDMI 2
HDMI 1 / MHL
USB TYPE B
USB wireless adapter (optional)
USB storage device

F-6


AUDIO OUT
COMPUTER IN 2 / MONITOR OUT
VIDEO IN
AUDIO IN 2
L
R
USB TYPE A DC5V 0.5A
LAN
AUDIO IN 1
CONTROL
MIC
HDMI 2
DISPLAY
HDMI
USB TYPE A
Computer


F-7




[unit: mm]

F-8


(1)




(2)




(3)



(4)




(5)




(6)

Security label


(7)



(8)



(9)



(10)

