

F-1

• On a horizontal surface



F-2

• Mounted on the wall or ceiling




T-1 CP-AX2503, CP-AX3003, CP-AX3503 (1024 x 768) (±8%)

Screen size (diagonal) ⓐ		Projection distance				Screen height			
		ⓑ1		ⓑ2		ⓒ1		ⓒ2	
type(inch)	m	m	inch	m	inch	m	inch	m	inch
60	1.5	0.104	4.1	0.385	15.2	0.224	8.8	1.138	44.8
70	1.8	0.170	6.7	0.451	17.8	0.247	9.7	1.314	51.7
80	2.0	0.236	9.3	0.517	20.4	0.270	10.6	1.489	58.6
90	2.3	0.302	11.9	0.583	23.0	0.293	11.5	1.664	65.5
100	2.5	0.368	14.5	0.649	25.6	0.315	12.4	1.839	72.4


T-2 CP-AW2503, CP-AW3003 (1280 x 800) (±8%)

Screen size (diagonal) ⓐ		Projection distance				Screen height			
		ⓑ1		ⓑ2		ⓒ1		ⓒ2	
type(inch)	m	m	inch	m	inch	m	inch	m	inch
60	1.5	0.128	5.0	0.409	16.1	0.313	12.3	1.121	44.1
70	1.8	0.198	7.8	0.479	18.9	0.351	13.8	1.293	50.9
80	2.0	0.268	10.5	0.549	21.6	0.388	15.3	1.465	57.7
90	2.3	0.338	13.3	0.619	24.4	0.426	16.8	1.638	64.5
100	2.5	0.408	16.1	0.689	27.1	0.464	18.3	1.810	71.3


F-3


Computer
AUDIO OUT
L
R
VIDEO
COMPONENT
Y
Cb/Pb
Cr/Pr
HDMI
AUDIO OUT
AUDIO IN 1
COMPUTER IN 1
CONTROL
AUDIO IN 2
L
R
VIDEO IN
USB TYPE A
DC5V 0.5A
LAN
MIC
USB TYPE B
AUDIO OUT
DISPLAY
RS-232C
USB (A)
HDMI
VCR/DVD/Blu-ray
Disc player


F-4


Microphone system
Speakers
(with an amplifier)
R
L
Monitor
RGB IN
AUDIO IN 1
COMPUTER IN 1
CONTROL
AUDIO IN 2
L
R
VIDEO IN
USB TYPE A
DC5V 0.5A
LAN
MIC
HDMI 2
HDMI 1
USB TYPE B

F-5


Computer
RS-232C
USB TYPE A
LAN
Access point
AUDIO OUT
COMPUTER IN 2 / MONITOR OUT
VIDEO IN
AUDIO IN 2
L
R
USB TYPE A
DC5V 0.5A
LAN
AUDIO IN 1
COMPUTER IN 1
CONTROL
MIC
HDMI 2
HDMI 1
USB TYPE B
USB wireless adapter (optional)
USB storage device


F-6



377
141
360
136

[unit: mm]


F-7

(1)







(2)




(3)



(4)




(5)



(6)

Security label

(7)



(8)

